

BOD INCUBATOR

Precision Temperature Control
for Reliable BOD Analysis

INTRODUCTION

Equipaxis BOD Incubator is a high-performance system designed to deliver precise and stable temperature conditions essential for accurate biochemical oxygen demand (BOD) analysis. With an advanced microprocessor-based control system, it ensures consistent temperature maintenance across extended incubation periods, making it ideal for environmental, research, and quality control laboratories.

Engineered for uniform airflow and energy-efficient operation, the incubator provides consistent testing conditions for every sample. Its robust construction, user-friendly interface, and flexible storage configuration make it a reliable solution for laboratories requiring accuracy, durability, and operational efficiency.

KEY FEATURES



Precision Temperature Control

Microprocessor-based PID controller for accurate temperature regulation.
Wide operating range from 5°C to 60°C.



Uniform Temperature Distribution

High-performance air circulation system ensures consistent conditions.
Minimizes variability and improves result accuracy.



Energy Efficient & Eco-Friendly Design

Optimized insulation reduces power consumption.
Supports cost-effective and sustainable lab operations.



User-Friendly Operation

Digital display with intuitive controls for easy monitoring.
Simplifies workflow and reduces manual effort.



Robust & Durable Construction

Stainless steel inner chamber for hygiene and longevity.
GI powder-coated outer body for enhanced durability.



Flexible Storage Configuration

Removable stainless steel shelves for versatile sample placement.
Suitable for varied sample sizes and applications.



Enhanced Visibility & Convenience

Internal LED illumination for clear sample viewing.
Acrylic inner door for safe monitoring.



Precision You Can Measure. Reliability You Can Trust.

SPECIFICATIONS

Working Temperature Range	5°C to 60°C
Temperature Accuracy	±1°C
Temperature Controller	PID Microprocessor Controller
Temperature Uniformity	High uniformity with air circulation
Shelves	2 Wire Mesh
Type of Shelves	Removable
Material of Shelves	Stainless Steel (SS)
Air Circulation	Air Circulating Fan
Illumination	LED Light inside the chamber for sample viewing
Display	Digital Display
Material of Inner Chamber	Stainless Steel
Material of Outer Body	GI sheet powder coated
Insulation	Glass wool / PUF Insulation
Inner Door Material	Acrylic Sheet
Power Supply	220/230V AC

AVAILABLE MODELS

Model No	Chamber Dimensions (WxDxH)	Chamber Capacity	Shelves
EA151	450X450X760mm 6cu ft	160 Ltr	2
EA152	560X560X760mm 8cu ft	235 Ltr	2
EA153	600X600X800mm 10cu ft	300 Ltr	3
EA154	600X600X900mm 12cu ft	340 Ltr	3

SAFETY FEATURES

- ▶ PID Microprocessor Temperature Controller
- ▶ High Uniformity Air Circulation System
- ▶ Glass Wool / PUF Insulation Protection
- ▶ Stainless Steel Inner Chamber Construction
- ▶ Acrylic Inner Door for Safe Sample Monitoring



Scan to know more

Precision You Can Measure. Reliability You Can Trust.